



SUPERIOR
BUILDING
SOLUTIONS

SY No 117/120, Gandhi Maisamma Temple Road,
Gandhi Maisamma, Hyderabad, Telangana, INDIA - 500043

9154817016

nbssales@nandhigroup.com

<https://nandhigroup.com>



Tilonfix - NB-307

"Tile Adhesive (Type-I) is your ultimate solution for effortless and reliable tile fixing. This next-generation, ready-to-use thin-bed adhesive simplifies installation while delivering exceptional strength and durability. Made with high-quality OPC 53-grade cement and enriched with advanced polymers, it ensures a superior bond that lasts. Whether for walls or floors, indoors or outdoors, Tile Adhesive (Type-I) offers professional-grade performance you can trust every time."

Packing : 20/40 kg Bag

Colour : Grey

Coverage : Approx 3kg/m² @3mm thickness

Key Benefits

- Ready-to-Use Dry Mix
- Strong Bonding Strength
- Time-Saving Application
- Reduces Material Wastage
- Ideal for Vertical & Horizontal Surfaces
- Improved Workability
- Moisture & Heat Resistant
- Environmentally Friendly

Application Areas

- Suitable for Ceramic wall tiles
- Ceramic floor tiles (light duty)
- Glazed tiles
- Mosaic tiles (Size Small/Medium)



Wallfix - NB-315

"N-Bond Plus Extra Premium Tile Adhesive (Type-II) is the professional's choice — a high-performance, single-component thin-bed adhesive that ensures faster installation, stronger bonds, and worry-free results."

Packing : 20/40 kg Bag

Colour : Grey

Coverage : Approx 3kg/m² @3mm thickness

Key Benefits

- Strong Bonding Strength
- Larger Tile Support
- Interior & Exterior Use
- Water & Heat Resistance
- Cost-Effective in the Long Run
- Thin-Bed Application
- Reduced Shrinkage & Cracks
- Time & Labor
- Versatility
- Improved Aesthetics

Application Areas

- Medium to Large Format Tiles
- Wet & Damp Areas
- Heavy Traffic Zones
- Facade & External Cladding
- Tile-on-Tile Applications
- Cementitious & Concrete Surfaces
- Residential Flooring



Stonofix - NB-325

"Engineered for excellence, Tile Adhesive (Type-III) is a next-generation dry mix mortar for all tile and stone applications. From interiors to demanding surfaces, it delivers superior adhesion and heavy-duty performance you can trust."

Packing : 20/40 kg Bag

Colour : Grey

Coverage : Approx 3kg/m² @3mm thickness

Key Benefits

- High Bonding Strength
- Supports Large Format Tiles
- Heavy-Duty Performance
- Interior & Exterior Use
- Water & Heat Resistance
- Multi-Surface Compatibility
- Durable & Long-Lasting

Application Areas

- Large-Format Tiles & Stones
- Heavy-Duty Flooring
- Wet & Immersed Areas
- Exterior Cladding & Facades
- Countertops & Kitchen Platforms
- Vertical & Horizontal Surfaces
- Residential & Commercial Projects
- Tile-on-Tile Application



GTA-NB-335

“Build with confidence using (Type-IV) Tile Adhesive — a high-strength, easy-to-use adhesive for large tiles, glass mosaics, and stones. From kitchens and bathrooms to pools and outdoor spaces, it ensures long-lasting beauty and performance in any setting.”

Packing : 20/40 kg Bag
Colour : Grey / White
Coverage : Approx 3kg/m² @3mm thickness

Key Benefits

- High Polymer Strength
- Indoor & Outdoor Performance
- Water & Submersion Resistant
- Supports Heavy & Large Tiles
- Versatile Substrate Compatibility
- Tile-on-Tile Application
- Durable & Long-Lasting.
- Thin-Bed Technology
- Withstands Thermal & Structural Stress
- All-Purpose Solution



Application Areas

- Large-Format Tiles & Stones
- Countertops & Platforms
- Wet & Submerged Areas
- Tile-on-Tile Fixing
- Interior & Exterior Installations
- High-Traffic Areas
- Outdoor Applications
- Specialty Surfaces

Wall Texture (Fine, Regular & Jumbo)

“N Bond Wall Texture is a premium acrylic-based wall finish designed for durable, aesthetic surfacing to any construction project. It suits both interior and exterior walls, including plaster, concrete, and cement boards common in Indian homes and commercial buildings. Ideal for humid climates and effective at resisting algae and fungal growth.”

Forms & Pack Sizes

Available in powder form for easy on-site mixing with water. Standard pack sizes include 20kg bags for bulk projects and 5kg pails for smaller interiors or touch-ups.

Applications

Interiors: Over Primed Plaster In Living Rooms, Bedrooms,
Offices: low-voc, Acoustic Enhancement, Hides Imperfections.
Exteriors: Facades, Boundary Walls,
Elevations: withstands Monsoons & UV.

Advantages

- Water-Resistant & Superior Bonding
- Cover all undulations
- Ideal for Interior & Exterior Walls
- Resistance to Fading
- Long-lasting Durability
- Resist the micro cracks in plastering
- Custom textures like sand, stipple, or swirl patterns can be achieved by varying application tools.



Block Jointing Mortar

“Block jointing mortar is a superior Polymer modified OPC 53' grade cement-based mortar designed specifically for joining AAC blocks. This mortar is specially designed & manufactured to provide superior adhesive strength and a strong bond between the blocks.”

Forms : Grey Dry Powder
Pack Size : 40kg
Application : AAC Blocks, CLC, Concrete Blocks

Key Benefits

- No curing required
- Very high adhesion strength
- High compressive & tensile strength
- Durable, Fast & Economical
- No Wastage & Easy to use
- Seepage water percolation through joints is negligible



Coverage	Block Size	4"	6"	8"	9"
	No. of Blocks	80-90	50-60	40-50	30-40

NB-2K -Epoxy Grout

“Transform your tiling projects with our advanced 2-component Epoxy Grout — a high-performance solution crafted to enhance both beauty and durability. Versatile and reliable, it delivers a flawless finish with superior compatibility across a wide range of tile types.”

Packing : 5/10/20 kg Tin
Colour : As per customer requirement

Coverage	Tile Size	600X600	300X300	300X200	200X150	150X150	100X100
	Coverage for 2mm joint	8mm	6mm	6mm	5mm	4mm	4mm
		118	78	65	54	60	54

Advantages

- Exceptional Bond Strength
- Waterproof & Moisture Resistant
- Chemical & Stain Resistant
- Hygienic & Anti-Bacterial
- Smooth & Attractive Finish
- Versatile Application
- Durability in High-Traffic Areas
- Low Maintenance
- Color Stability
- Tile Protection

Application Areas

- Bathrooms & Kitchens
- Swimming Pools, Fountains & Spas
- Commercial Kitchens & Food Processing Units
- Hospitals, Clinics & Laboratories
- Residential Living & Decorative Spaces
- Industrial Applications
- High-Traffic Zones
- Countertops & Worktops
- Outdoor Tiling
- Glass Mosaics & Designer Tiles



NB-3K -Epoxy Grout

“Epoxy Tile Grout is a high-quality grouting solution made with resin, hardener, and colored filler powder. It not only seals gaps between tiles securely but also adds a stylish finish that's stain-resistant, waterproof, and long-lasting.”

Packing : 5/10/20 kg Tin
Colour : As per customer requirement

Coverage	Tile Size	600X600	300X300	300X200	200X150	150X150	100X100
	Coverage for 2mm joint	8mm	6mm	6mm	5mm	4mm	4mm
		118	78	65	54	60	54

Advantages

- High Strength & Durability
- Waterproof & Moisture Resistant
- Stain & Chemical Resistant
- Hygienic & Easy to Clean
- Color Consistency
- Versatile Application
- Long-Lasting Finish
- Resistance to Wear & Tear

Application Areas

- Bathrooms & Kitchens
- Swimming Pools & Fountains
- Commercial Kitchens & Food Processing Units
- Hospitals & Laboratories
- High-Traffic Zones
- Industrial Areas
- Living & Decorative Spaces
- Countertops & Worktops



N-BOND Cleaning Agent

Heavy-Duty Liquid Cleaner

“Non-toxic, neutral pH cleaner specially formulated for effective and safe cleaning of tiles, natural stones, grouts, and masonry surfaces. Powerful enough to remove tough stains.”

Packing : 1 Ltrs, 5 Ltrs, 20 Ltrs, 240Ltrs.

Key Benefits

- Removes Ement Stains, Concrete Residues, & Dust
- Prepares surfaces for coatings/repairs
- Cleans tools & Equipment
- Safe for ceramic tiles/granite in food industry

Application Areas

- Ceramic, Vitrified, Porcelain Tiles.
- Natural Stones (marble, Granite – Dilute Use).
- Grout Lines, Bathroom/Kitchen Floors, Swimming Pools.
- Post-Tiling Construction Cleanup.



N Bond Primer Coat - SB105

Solvent-based Epoxy Impregnating Primer

"Two-component epoxy resin impregnating coat designed for sealing and protecting concrete and screed surfaces. Provides effective protection against light to medium mechanical loads and penetrates well into cement-bound surfaces."

Application Method: Brush or roller application

Key Benefits:

- Effective surface sealing & protection
- Penetrates cement-bound surfaces
- Enhances adhesion & durability
- Pre-treatment for epoxy floor coatings
- Ideal for old & porous concrete
- Superior surface preparation

Application Areas

- Old & porous concrete floors
- Finished screeds
- Repair & maintenance of aged surfaces
- Pre-treatment for epoxy floor coatings.



N Bond Epoxy Coat - HB103

High-build Epoxy Floor Coating for Industrial & Commercial Use

"Two-component high-build epoxy floor coating system made of liquid epoxy resin and hardener. Forms a hard, tough, and durable surface with superior adhesion and excellent mechanical and chemical resistance."

Application Method: Brush or Roller Application

Key Benefits:

- Solvent-free & Seamless finish
- Excellent chemical resistance to acids, alkalis, oils & solvents
- Weather-resistant & suitable for varied environments
- Durable with low maintenance requirements
- High mechanical strength & Abrasion resistance
- Available in a range of colors for aesthetics

Application Areas

- Hotels & Restaurants
- Dairies & Beverage bottling plants
- Battery rooms, Chemical manufacturing plants
- Hospitals & Laboratories
- Sewage & Water treatment plants
- Garages, Workshops
- Oil Refineries & Power stations
- Food processing & Pharmaceutical industries
- Structural steel protection in industrial environments



Unsanded Grout

“Unsanded Grout is a high-quality formulation of white cement, refined polymers, and premium minerals. Specially engineered for narrow joints up to 3 mm, it pairs effortlessly with Bond Grout Admix Plus to deliver a sleek, durable, and elegant finish on porous and absorbent tiles.”

Packing : 1/10/20 kg Bag

Colour : As per customer requirement

Recommended to add admix grout instead of water for better performance.

Key Benefits

- Smooth Finish
- Ideal for Narrow Joints
- Easy to Apply & Clean
- No Shrinkage Cracks
- Premium Strength & Durability
- Perfect for Porous & Absorbent Tiles
- Excellent Adhesion with Admix
- Aesthetic Appeal



Application Areas

- Bathrooms & Kitchens
- Outdoor Tiling
- Industrial Applications
- Hospitals, Clinics & Laboratories
- High-Traffic Zones
- Commercial Kitchens & Food Processing Units
- Residential Living & Decorative Spaces
- Countertops & Worktops
- Swimming Pools, Fountains & Spas
- Glass Mosaics & Designer Tiles

Unsanded Grouts Admixture

“Enhance your tiling projects with our advanced Grout Admixture — a high-performance solution engineered to boost both durability and aesthetics. Designed for seamless compatibility with a wide range of tiles, it ensures stronger joints, longer life, and a flawless finish every time.”

Packing : 1 Ltrs, 5 Ltrs, 10 Ltrs

Dosage : 400ml per 1kg of Unsanded Grouts

Key Benefits

- Enhanced Strength
- Water Resistance
- Stain & Dirt Resistance
- Improved Flexibility
- Better Workability
- Superior Adhesion
- Cost-Effective Upgrade



N Bond Conproof - IWPL

Liquid Integral Waterproofing Compound

“A liquid waterproofing additive made from modified plasticizers, specially formulated to integrate easily with concrete and cement mortars from within.”

Consumption: 200 ml per 50 kg cement

Pack Sizes: 1Ltrs, 5Ltrs, 20Ltrs, 240Ltrs

Application: Add directly into dosing/gauging water

Key Benefits:

- Mixes instantly with water, no lumps.
- Cuts water absorption and leakage.
- Improves workability, cohesion & strength.
- Minimizes shrinkage cracks.
- Chloride-free, safe for RCC.

Application Areas:

- Roofs & Terraces.
- Masonry & Plaster Mortars.
- Basements & Rafts.
- Sunken Slabs, Bathrooms, Wash Areas.
- Water Tanks & Retaining Walls.



N Bond Aqua Coat - 2K


Two-Component High-Performance Cementitious Waterproofing System

"Two-component elastomeric waterproofing system formulated using modified acrylic polymer emulsion and specially selected cementitious powders. Provides excellent flexibility, adhesion, and resistance to both positive and negative water pressure."

Coverage: 1.0-1.5 kg/m² at 1mm thickness in two coats

Pack Size: 20 kg set (Powder + Liquid)

Application Method: Brush or roller application



Key Benefits:

- Strong adhesion even on damp surfaces.
- Resists positive and negative water pressure.
- Flexible, bridges hairline cracks.
- Suitable for internal & external areas.
- Brush/roller friendly, non-toxic for potable water.

Application Areas:

- Terraces & Roofs.
- Bathrooms & Wet Areas.
- Water Tanks And Swimming Pools.
- Basements & Retaining Walls.
- Planter Boxes & Wet Rooms.

N Bond Contuff - GP2

High Strength, Non-shrink, Free-flow Precision Grout

"Ready-to-use high-performance non-shrink cementitious grout specially formulated for precision grouting of heavy machinery and equipment foundations. Consists of Portland cement, graded fillers, selected aggregates, and chemical additives that provide controlled expansion."

Pack Size: 25 kg

Mix Usage: Use within 30 minutes of preparation

Curing: Keep surface moist for minimum 24 hours

Coverage: Varies with application requirements

Key Benefits:

- Chloride-free, durable under heavy loads.
- Excellent flow for easy placement.
- Controlled expansion for precision grouting.
- Non-shrink, maintains full contact.
- High early strength for quick commissioning.

Application Areas

- Machine & Equipment Foundations.
- Compressors, DG Sets, Anchor Bolts.
- Gaps Under Columns & Base Plates.
- Heavy machinery bases
- Crane & transport rails.



N Bond Crack Filling - Powder

Polymer-Modified Cementitious Crack Repair Mortar

"Single-component polymer-modified cement-based crack repair compound designed for internal and external surface cracks. When mixed with water, it forms a high-strength, durable mortar with excellent bonding to concrete, cement plaster, and masonry surfaces"

Coverage: 1.0-1.5 kg/m² at 1mm thickness in two coats

Pack Size: 1kg, 10kg, 20kg.

Application: Apply in two coats for best results

Key Benefits:

- Strong adhesion with flexible crack filling.
- Compatible with all cement-based surfaces.
- Crack-resistant, low-shrink formulation.
- Works on vertical & horizontal areas.
- Easy mixing, suitable for thin skim coats.

Application Areas

- Fine and medium surface cracks.
- Hairline cracks in walls and ceilings.
- Leveling uneven patches & imperfections.
- Pre-paint crack filling.
- Surface preparation.



N Bond Conbond - SBR

High-Performance SBR Latex for Concrete Bonding and Mortar Modification

"Premium Styrene Butadiene Rubber latex-based emulsion designed to improve the bonding, flexibility, and durability of cementitious mixes. Formulated with high-grade acrylic and SBR polymers for enhanced performance."

Coverage: 4-5 m² per coat when used as bonding agent

Consumption for Mortar: 4-5 kg per 50 kg cement (standard), 8-10 kg per 50 kg cement (structural repair)

Pack Sizes: 1kg, 5kg, 20kg.

Key Benefits:

- Strong bond between old & new concrete.
- Boosts flexural & tensile strength.
- Enhances waterproofing & chemical resistance.
- Reduces shrinkage & cracking.
- Ideal for repair mortars & bonding coats.

Application Areas:

- Concrete Repairs & Patching.
- Bonding new concrete/mortar to old.
- Waterproof Plasters & Screeds.
- Polymer-modified mortars & Toppings.
- Industrial, High-wear floors.



Our Esteemed Clients & Trusted Partners

